



# Preliminary Data Sheet

## UDMAX™ GFRPP 45-70 TAPE (0.25 mm)

### DESCRIPTION

UDMAX™ GFRPP 45-70 TAPE is a developmental flame retardant UD glass reinforced, polypropylene based, composite material, produced using FRT's proprietary HPFIT™ technology, delivering optimal fiber spreading and a resin-rich surface layer at high fiber contents. UDMAX™ GFRPP 45-70 TAPE offers a combination of high strength and stiffness, which can result in weight reduction and overall customer product performance improvement. This tape has been developed for the production of lightweight sandwich panels for the railway industry. Panels made with this product can comply with the EU fire safety standard EN45545-2. Please contact our customer service department for available colors, tape length and width, as well as winding method.

### TYPICAL PROPERTIES VALUES

(Revision: 20200708)

Name	Typical values	Unit	Test methods
<b>PHYSICAL</b>			
Glass content	45	Volume%	-
Glass content	70	Weight%	-
Thickness	0.250	mm	-
Density	1.66	kg/dm <sup>3</sup>	ISO1183
Areal weight	415	g/m <sup>2</sup>	-
<b>MECHANICAL</b>			
Tensile modulus 0°	36	GPa	ISO 527-5
Tensile strength 0°	675	MPa	ISO 527-5

### PROCESSING

It is not necessary to dry UDMAX™ GFRPP 45-70 TAPE prior to use. The recommended maximum processing temperature 220°C. It is advised to allow newly shaped parts, produced using UDMAX™ GFRPP 45-70 TAPE, to cool down to 65°C or below, before further handling.

#### DISCLAIMER

Information and recommendations contained in this document are given in good faith. However, seller makes no express or implied representation, warranty or guarantee (i) that any results described in this document will be obtained under end use conditions, or (ii) as to the effectiveness or safety of any design or application incorporating seller's materials, products, services or recommendations. Brands marked with ™ are registered trademarks of FRT Tapes.